



Super TT

Applications

Castrol Super TT is a quality 2-stroke engine oil, specially formulated to provide long term engine protection. It also prevents ring sticking throughout the life of the engine whilst minimising smoke emissions to an acceptable level.

Castrol Super TT is suitable for both oil injection and pre-mix lubrication and can be used up to a fuel/oil ratio of 50:1 or ratios recommended by engine manufacturers.

Castrol Super TT is recommended for on-road motorcycles and mopeds

Features / Benefits

a mineral based 2-stroke engine oil
designed for both oil injection and pre-mix lubrication up to a ratio of 50:1
durable protection against piston ring sticking
internal engine cleanliness
minimises smoke emissions

Specifications / Performance

JASO FB

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Super TT

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products.

Castrol (UK) Ltd. or its subsidiaries will not accept liability if the product is used other than in the manner or with the precautions or for the purpose/s specified. Before the product is used other than as directed, advice should be obtained from the local Castrol office.

Typical Characteristics

	Test Methods	Units	Value:
--	--------------	-------	--------

SAE

<i>Test</i>	<i>Method(s)</i>	<i>Unit</i>	<i>Typical</i>
Appearance	Visual		Bright and clear
Colour			Red
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	11.0
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	94.2
Viscosity Index	ASTM D2270		103
Calcium, % wt	ASTM D4951	% wt	0.58
Phosphorus, % wt	ASTM D4951	% wt	0.005 max
Zinc, % wt	IP 308	% wt	0.005 max

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

This Data sheet and information it contains is considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication.

It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid licence.

The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned).

Castrol (UK) Ltd
Wakefield House
Pipers Way
Swindon
Wiltshire
SN3 1RE

Lubricants Helpline : 01793 452222
Orders/Enquiries: 08459 123011
